

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) A process, comprising:
~~for~~ converting digital video signals having images organized in blocks of pixels between a first format and a second format, said second format being a format compressed via vector quantization, ~~the process comprising~~ said converting including:
obtaining said vector quantization from repeated application of a scalar quantizer to the pixels of said blocks with a quantization step determined in an adaptive way according to characteristics of the pixels, wherein said obtaining said vector quantization includes:
identifying a sharpness value of edges in each of said blocks of pixels, and
quantizing said sharpness value to divide the edges into a number of classes; and
attributing a value to said quantization step differentiated according to the
classes, wherein the value of the quantization step is increased near the edges of said
images having said pixels.
2. (Original) The process according to claim 1 wherein said quantization step is determined so as to increase according to a lack of uniformity of the pixels in the block.
3. (Original) The process according to claim 2 wherein said quantization step is determined by a law increasing according to multiples.
4. (Currently Amended) The process according to claim 1, ~~further comprising wherein said converting includes~~ detecting a level brightness of pixels in a block and determining said quantization step in such a way that said quantization step increases as a function of said level of brightness.

5. (Currently Amended) The process according to claim 1, ~~further comprising wherein said converting includes:~~

detecting a lack of uniformity of the pixels in a block;
detecting a level of brightness of the pixels in the block; and
determining said quantization step in such a way that said quantization step first increases and then decreases as a function of said lack of uniformity and said level of brightness.

6. (Original) The process according to claim 5 wherein said quantization step is made to increase and decrease by multiples or sub-multiples.

7. (Original) The process according to claim 4 wherein detecting the level of brightness of the pixels in the block is carried out by detecting a mean level of brightness of the pixels in the block.

8. (Original) The process according to claim 1, wherein in passage from said first format to said second format, said digital video signals are subjected to at least one of the following:

sub-sampling;
low-pass filtering for anti-aliasing purposes before sub-sampling; and
multiplexing of at least one part of digital data necessary for representation of an image.

9. (Original) The process according to claim 1 wherein the digital video signals include multiplexed chromatic components, wherein in passage from said first format to said second format, the process further comprising re-ordering the pixels in each block to be quantized by composing them in a vector such that the multiplexed chromatic components are quantized separately.

10. (Currently Amended) The process according to claim 1, ~~further comprising wherein said converting includes~~ identifying, in a context of said digital video

signals, blocks of uniform pixels, choosing for said blocks of uniform pixels a minimum quantization step among quantization steps adopted in said vector quantization.

11. (Original) The process according to claim 1 wherein said digital video signals in said second format are expressed in a form of binary codes associated to respective quantized signals, the process further comprising executing a function of prediction of said binary codes.

12. (Original) The process according to claim 11 wherein said function of prediction of the binary codes is carried out according to a DPCM scheme.

13. (Original) The process according to claim 1 wherein in passage from said first format to said second format, the signal compressed via vector quantization is subjected to entropic encoding.

14. (Original) The process according to claim 13 wherein said entropic encoding is performed with a technique chosen from at least one of run-length encoding, Huffmann encoding, and arithmetic encoding.

15. (Original) The process according to claim 1 wherein said vector quantization is a multi-dimensional vector quantization resulting from concatenation of a plurality of vector quantizations, each resulting from repeated application of a scalar quantization.

16. (Original) The process according to claim 15 wherein for each of said concatenated vector quantizers, binary codes of reconstruction points are assigned in such a way that the reconstruction points with small distance in multi-dimensional space have binary codes with small difference.

17. (Currently Amended) The process according to claim 1 wherein said vector quantization is obtained with application of two scalar quantizers with quantization steps scaled by the constants $2/3$ and $\sin(\pi/3)$.

18. (Currently Amended) The process according to claim 17, ~~further comprising wherein said converting includes~~ defining points of reconstruction allowed so that these points will form a hexagonal lattice.

19. (Canceled)

20. (Currently Amended) The process according to claim ~~19-1~~ wherein said quantization step is determined according to at least one law chosen from the following:

$$m \cdot E_Q + q; \text{ and}$$

$$m \cdot (t \wedge E_Q) + q;$$

where m and q are constants, determined selectively, and E_Q is an index which identifies said edge classes, and t is a scalar value.

21. (Currently Amended) The process according to claim 4, ~~further comprising wherein said converting includes:~~

dividing said level of brightness of the pixels in the block in a number of classes;
and

selecting a value of said quantization step in a different way according to the classes thus determined.

22. (Original) The process according to claim 1 wherein said video signals in said first format are signals generated according to a so-called Bayer pattern, which can be ordered in blocks of size 4×2 having the following pattern of chromatic components:

$$\text{row 1} = G_1 R_1 G_2 R_2,$$

$$\text{row 2} = B_1 G_3 B_2 G_4;$$

and wherein said vector quantization is a two-dimensional vector quantization applied to pairs $\langle R_1, R_2 \rangle$, $\langle B_1, B_2 \rangle$ together with $\langle G_1, G_2 \rangle$, $\langle G_3, G_4 \rangle$ or $\langle G_1, G_3 \rangle$, $\langle G_2, G_4 \rangle$.

23. (Original) The process according to claim 1 wherein said digital video signals in said first format are digital video signals in the RGB format and wherein said digital video signals in said second format are subjected to a change of co-ordinates to a color space chosen from at least one of YCbCr, YUV, UIQ, and YDbDr.

24. (Original) The process according to claim 1 wherein said vector quantization is applied to adjacent pairs of pixels in a luminance plane.

25. (Original) The process according to claim 8 wherein in said digital video signals in said second format, chrominance planes are sub-sampled according to a quincunx pattern.

26. (Currently Amended) A system for converting digital video signals having images organized in blocks of pixels between a first format and a second format, said second format being a format compressed via vector quantization, the system comprising:

at least one converter chosen between an encoder and a decoder and wherein said converter is configured for a vector quantization resulting from repeated application of a scalar quantizer to the pixels of said blocks with a quantization step determined in an adaptive way according to characteristics of the pixels, wherein said converter is configured to:

identify a sharpness value of edges in each of said blocks of pixels, and quantize said sharpness value to divide the edges into a number of classes; and

attribute a value to said quantization step differentiated according to the classes, wherein the value of the quantization step is increased near the edges of said images having said pixels.

27. (Original) The system according to claim 26 wherein said converter is configured to determine said quantization step in such a way that said quantization step increases according to a lack of uniformity of the pixels in a block.

28. (Original) The system according to claim 27 wherein said converter is configured to determine said quantization step by a law increasing according to multiples.

29. (Original) The system according to claim 26 wherein said converter is configured to detect a level of brightness of pixels in a block and determine said quantization step in such a way that said quantization step grows as a function of said level of brightness.

30. (Original) The system according to claim 26 wherein said converter is configured to:

detect a lack of uniformity of the pixels in a block;

detect a level of brightness of the pixels in the block; and

determine said quantization step in such a way that said quantization step first increases and then decreases as a function of said lack of uniformity and said level of brightness.

31. (Original) The system according to claim 30 wherein said converter is configured to increase and decrease said quantization step by multiples or sub-multiples.

32. (Original) The system according to claim 29 wherein said converter is configured to detect a level of brightness of the pixels in the block by detecting a mean level of brightness of the pixels in the block.

33. (Original) The system according to claim 26 wherein said converter is an encoder configured to subject said digital video signals to at least one operation chosen from:

sub-sampling;

low-pass filtering for anti-aliasing purposes before sub-sampling; and

multiplexing of at least one part of digital data necessary for representation of an image.

34. (Original) The system according to claim 26 wherein the digital video signals comprise multiplexed chromatic components, wherein said encoder is configured to re-order the pixels in each block to be quantized by composing them in a vector such that the multiplexed chromatic components are quantized separately.

35. (Original) The system according to claim 26 wherein said encoder is configured to identify, in a context of said digital video signals, blocks of uniform pixels and to choose for said blocks of uniform pixels a minimum quantization step among quantization steps adopted in said vector quantization.

36. (Original) The system according to claim 26 wherein said converter is configured in such a way that said digital video signals in said second format are expressed in a form of binary codes associated to respective quantized signals and wherein said converter is configured to execute a function of prediction of said binary codes.

37. (Original) The system according to claim 36 wherein said function of prediction of the binary codes is carried out according to a DPCM scheme.

38. (Original) The system according to claim 26 wherein said converter is configured to subject the signals converted from said first format to said second format to a function of entropic encoding or decoding.

39. (Original) The system according to claim 38 wherein said entropic encoding is performed with a technique chosen from at least one of: run-length encoding, Huffmann encoding, and arithmetic encoding.

40. (Original) The system according to claim 26 wherein said converter is configured for a vector quantization having a multi-dimensional vector quantization resulting from concatenation of a plurality of vector quantizations, each resulting from repeated application of a scalar quantization.

41. (Original) The system according to claim 40 wherein said converter is configured to assign binary codes of reconstruction points for each of said concatenated vector quantizations in such a way that the reconstruction points with small distance in a multi-dimensional space have binary codes with small difference.

42. (Original) The system according to claim 26 wherein said converter is configured to obtain an application of two scalar quantizers with quantization steps scaled by constants $2/3$ and $\sin(\pi/3)$.

43. (Original) The system according to claim 42 wherein said converter is configured to define points of reconstruction allowed so that these points will form a hexagonal lattice.

44. (Canceled)

45. (Currently Amended) The system according to claim ~~44~~26 wherein said converter is configured to determine said quantization step (Q) according to at least one law chosen from:

$$m * E_Q + q; \text{ and}$$

$$m * (t^{\wedge} E_Q) + q;$$

where m and q are constants, determined selectively and E_Q is an index which identifies said edge class, and t is a scalar value.

46. (Original) The system according to claim 29 wherein said converter is configured to:

divide said level of brightness of the pixels in the block into a number of classes;

and

select a value of said quantization step in a differentiated way according to the classes thus determined.

47. (Currently Amended) The system according to claim ~~25~~26 wherein said video signals in said first format are signals generated according to a so-called Bayer pattern, which can be ordered in blocks of size 4x2 having the following pattern of chromatic components:

row 1 = $G_1R_1G_2R_2$

row 2 = $B_1G_3B_2G_4$

and wherein said vector quantization is a two-dimensional vector quantization applied to pairs $\langle R_1, R_2 \rangle$, $\langle B_1, B_2 \rangle$ together with $\langle G_1, G_2 \rangle$, $\langle G_3, G_4 \rangle$ or $\langle G_1, G_3 \rangle$, $\langle G_2, G_4 \rangle$.

48. (Original) The system according to claim 26 wherein said digital video signals in said first format are digital video signals in an RGB format and wherein said digital video signals in said second format are subjected to a change of co-ordinates to a color space chosen from at least one of YCbCr, YUV, UIQ, and YDbDr.

49. (Original) The system according to claim 26 wherein said vector quantizer is applied to adjacent pairs of pixels in a luminance plane.

50. (Original) The system according to claim 26 wherein in said digital video signals in said second format, chrominance planes are sub-sampled according to a quincuncial pattern.

51. (Currently Amended) An article of manufacture, comprising:

a ~~machine~~computer-readable medium ~~having encoded with a computer program~~
representing instructions stored thereon to cause a processor to:

convert a digital video signal having images organized in blocks of pixels from a first format to a second format, including instructions to use vector quantization to compress the first format into the second format, ~~and, including instructions to cause said processor~~ to obtain the vector quantization, repeatedly apply a scalar quantizer to the pixels of the blocks with an adaptive quantization step based on characteristics of the pixels, wherein the instructions to obtain the vector quantization include instructions to:

identify a sharpness value of edges in each of said blocks of pixels, and
quantize said sharpness value to divide the edges into a number of classes; and

attribute a value to said quantization step differentiated according to the
classes, wherein the value of the quantization step is increased near the edges of said
images having said pixels.

52. (Currently Amended) The article of manufacture of claim 51 wherein ~~the machine-readable medium further~~said instructions to convert ~~includes include~~ instructions ~~stored thereon~~ to simultaneously reduce statistical and perceptive redundancy of data in the video signal.

53. (Currently Amended) The article of manufacture of claim 51 wherein ~~the machine-readable medium further~~ said instructions to convert ~~includes include~~ instructions ~~stored thereon~~ to change the quantization step based on at least one of lack of uniformity of pixels in a block and a level of brightness of the pixels in the block.

54. (Currently Amended) The article of manufacture of claim 51 wherein the video signals include multiplexed chromatic components, and wherein the ~~machine~~computer-readable medium further includes instructions stored thereon to ~~quantized~~ quantize the chromatic components separately.

55. (Currently Amended) The article of manufacture of claim 51 wherein ~~the machine-readable medium further said instructions to convert~~ includes ~~includes~~ instructions ~~stored thereon~~ to concatenate a plurality of vector quantizations to obtain a multi-dimensional vector quantization, each of the vector quantizations resulting from repeated application of a scalar quantization.

56 - 57. (Canceled)

58. (Currently Amended) A system, comprising:

a means for receiving a digital video signal organized into blocks of pixels at a first format and for outputting the digital video signal at a second format;

a means for encoding the digital video signal from the first format to the second format; ~~and, said means for encoding including~~ a means for performing vector quantization to compress the digital video signal at the first format into the second format using repeated application of a scalar quantizer to the pixels of the blocks, ~~including a means for with adaptively determining~~ a quantization step adaptively determined based on characteristics of the pixels, the means for performing vector quantization including:

means for identifying a sharpness value of edges in each of said blocks of pixels, and quantizing said sharpness value to divide the edges into a number of classes;
and

means for attributing a value to said quantization step differentiated according to the classes, wherein the value of the quantization step is increased near the edges of said images having said pixels.

59. (Currently Amended) The system of claim 58 wherein the means for adaptively determining the quantization step include a means for changing the quantization step based on at least one of lack of uniformity of pixels in a block, and a level of brightness of pixels in the block, ~~and values of edge sharpness of an image.~~

60. (Currently Amended) The system of claim 58, ~~further comprising wherein~~
said means for encoding includes a means for quantizing multiplexed chromatic components of
the digital video signal separately.

61. (Currently Amended) The system of claim 58, ~~further comprising wherein~~
said means for encoding includes a means for executing a function of prediction of binary codes
that are associated to respective quantized signals and that are used to express the digital video
signals in the second format.

62. (Original) The system of claim 58 wherein the means for performing
vector quantization include a means for concatenating a plurality of vector quantizations, each
resulting from repeated application of a scalar quantization.